

VENOR



A clever wrapper always at your side. This is the way we think about C-One Venor: a quick and always ready machine that can actively improve the packaging process of its owner.

Thanks to its big autonomy, it is a perfect machine to deal with big workloads, while the many features of its software allows a plenty of solutions for all wrapping requiremnets. C-One Venor driving system makes this machine very stable and easy to move. Despite its dimensions the area which is necessary for wrapping cycle is quite small.

www.cecgroupsrl.com

Big autonomy
Full set of functions
Easy to drive

INVENTECH AS

Fjellhamarveien 52
NO-1472 Fjellhamar
Tel: +47 22 38 28 00
post@inventech.no
www.inventech.no

Technical Data

- Height: 2505 mm
- Width: 767 mm
- Length: 1808 mm
- Weight: 400 Kg
- Power supply: 2x12V AGM batteries VAC 3PH+N
- Power absorption: 2,5 Ah kW or 1kW

VENOR

PRODUCT SPECIFICATIONS

- Electronic printed circuit board for the management of the cycle
- Frequency controller for rotation speed adjustment (from 1,8 km/h to 4,9 km/h)
- Frequency controller for carriage speed adjustment (speed going up and speed going down can be set differently)
- Maximum wrapping height: 2400 mm
- Maximum size of the pallet: unlimited
- Electromagnetic brake for film stretching
- Photocell for pallet height detection
- Safety stop at the base of machine
- Power board ip54
- Touch screen
- Main parameters protected by password
- Main parameters adjustable by the control panel: cycle selection, bottom wraps, top wraps, rotation speed, carriage speed going up, carriage speed going down, film tension, photocell delay, starting height
- Reinforcing operation
- Working cycles:
 - up/down; topsheet; only ascent; only down
- 20 programs can be saved by the customer
- 3 working ways: manual, semiautomatic, fixed height
- Acoustic warning at the cycle beginning and stop
- Battery charge monitoring and warning message on the display when the battery is low
- Touching wheel with quick height adjustment
- Autodiagnostic
- Advanced battery charger with efficiency > 85%, charging process fully controlled by microprocessor, automatic reset after connecting a new battery, protection against polarity inversion and short circuits, autodiagnostic, compensation of the voltage drop on the battery cables, normally closed power contact
- Powder coating
- Braked arm at the end of the cycle
- 2 years warranty



Control Panel



Easy to drive



Big AGM Batteries
Li-Ion As Option



C&C group s.r.l.
via Calcinaro 2071
47521 Cesena (FC) - Italy
+39 (0)547 324747

P.IVA e Cod. Fisc. 03434700401
SDI: T04ZHR3
PEC: cecgroupsrl@pec.it
info@cecgroupsrl.com

INVENTECH AS
Fjellhamarveien 52
NO-1472 Fjellhamar
Tel: +47 22 38 28 00
post@inventech.no
www.inventech.no



www.cecgroupsrl.com